

# LOW PROFILE CYLINDER KIT

10 TON CAPACITY | 1.5" STROKE | 10,000 PSI MAX. PRESSURE




## FEATURES

- Designed for use in confined spaces
- Ideal for pushing applications
- Includes stackable adapters that fit into the base of the cylinder
- Industrial grade spring for increased spring performance
- Industrial grade steel construction withstands even the most demanding of applications
- Chrome plated piston rod eliminates corrosion and rust
- 3/8" NPTF female coupler and dust cap on all models

Adapter #	Length	Diameter
	(in.)	(in.)
1	0.98	1.75
2	1.97	1.75
3	2.95	1.75

					A	B	C	D	E	F	G	I		
Capacity	Stroke	Model #	Cylinder Effective Area	Oil Capacity	Collapsed Height	Extended Height	Outside Diameter	Cylinder Bore Dia.	Plunger Diameter	Base to Coupler Port	Saddle Distance above Cylinder	Saddle Diameter	Weight	
(tons)	(in.)		(in. <sup>2</sup> )	(in. <sup>3</sup> )	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(lbs.)	
10	1.51	SL101K	2.36	3.6	3.5	5.01	2.76	1.73	1.5	1.02	0.04	1.82	9.79	

 California residents - These products may contain a chemical known to cause cancer or reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

