


METAL RESERVOIR | 3/8"-18 NPTF PORTS | 10,000 PSI MAX. PRESSURE

METAL RESERVOIR | 3/8"-18 NPTF PORTS | 10,000 PSI MAX. PRESSURE

DOUBLE ACTING HAND PUMPS

FEATURES

- 4W3P valve for double acting cylinder applications
- High strength metal reservoir eliminates reservoir cracking
- 2 speed pump bodies for faster operation
- Ideal for frame machines and other OEM equipment
- Internal pressure relief valve protects from overloading
- Maximum working pressure at 10,000 psi
- Large reservoir capacities for larger applications



Model #	Usable Oil Capacity (in. <sup>3</sup> )	Valve Function	Pump Type	Pressure Rating		Oil Displacement Per Stroke		Maximum Operating Force (lbs.)	Piston Stroke	Oil Outlet Port	Weight (lbs.)
				1st Stage (psi)	2nd Stage (psi)	1st Stage (in. <sup>3</sup> )	2nd Stage (in. <sup>3</sup> )				
PH134D	122	Double Acting	2 Speed	400	10000	2.39	0.17	81	0.98	3/8"-18NPTF	30.21
PH427D	433	Double Acting	2 Speed	400	10000	6.81	0.25	78	1.26	3/8"-18NPTF	60.20

⚠ California residents - These products may contain a chemical known to cause cancer or reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

⚠ California residents - These products may contain a chemical known to cause cancer or reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

