

## HYDRAULIC HOSES



### 1/4" HOSES

Model #	Hose I.D. (in.)	Hose End Fittings	Operating Pressure (psi)	Hose Length (ft.)
H9462	1/4"	3/8"-18 NPTF	10,000	2
H9463	1/4"	3/8"-18 NPTF	10,000	3
H9446	1/4"	1/4"-18 NPTF	10,000	6
H9466	1/4"	3/8"-18 NPTF	10,000	6
H9468	1/4"	3/8"-18 NPTF	10,000	8
H94610	1/4"	3/8"-18 NPTF	10,000	10
H94612	1/4"	3/8"-18 NPTF	10,000	12
H94620	1/4"	3/8"-18 NPTF	10,000	20
H94630	1/4"	3/8"-18 NPTF	10,000	30



### 3/8" HOSES

Model #	Hose I.D. (in.)	Hose End Fittings	Operating Pressure (psi)	Hose Length (ft.)
H9666	3/8"	3/8"-18 NPTF	10,000	6
H96610	3/8"	3/8"-18 NPTF	10,000	10
H96620	3/8"	3/8"-18 NPTF	10,000	20
H96630	3/8"	3/8"-18 NPTF	10,000	30
H96650	3/8"	3/8"-18 NPTF	10,000	50

## F32 HYDRAULIC OIL (1 GALLON)

F32 HYDRAULIC FLUID SPECIFICATION CHART	
ISO Viscosity	32
Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	5.40
Kinematic Viscosity @ 40°C, cSt (ASTM D-445)	32.00
Viscosity Index (ASTM D-2270)	100
Turbine Oxidation (ASTM D-943)	5000
RPVOT, min (ASTM D-2272)	300
Emulsion Separation, min (ASTM D-1401)	10
Pour Point, °C (ASTM D-97)	-37
Flash Point, °F (ASTM D-92)	435



California residents - These products may contain a chemical known to cause cancer or reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)